

# Wascomat Super 200 G-Force Washers for OPL

**High-speed extraction Compass Control washers save time, water, and energy.**

Built to last, Wascomat's 200 G-Force solid-mount washers spin faster and remove more water. This results in less drying time and significant labor and energy savings. Hotels, motels, hospitals, nursing homes, restaurants, and other facilities can go right to flat-work finishing equipment after conditioning items in the dryer. You'll get superior results while saving time and money!



*Available in 20, 25, 30, 40, 55 and 75 lb. capacities. Stainless or white.*

## Dramatically different.

- Lowest water consumption in the industry.
- Installs on regular concrete pad or steel base.
- Single phase 120 or 220 volt electrical service reduces installation costs.
- Inverter driven motor for smooth operation and high efficiency.
- New soft-grip, slip-lock door handle for safe and trouble-free operation.
- Door unlocks immediately at the end of wash cycle.
- Unique 4-compartment supply dispenser lets you conveniently load all laundry supplies before starting the wash.
- Provisions to connect up to 5 liquid supplies.
- Specialty programs easily created in Wash Program Manager.
- Unibody construction eliminates welds for superior strength and durability.
- Interchangeable parts from one machine size to another.

## Features of Compass Control

- Customize wash programs to raise efficiencies and lower costs.
- Choose your display language.
- Total of 30 built in programs with room for 10 additional custom programs.
- Reduce operator error by allowing access only to the programs you use.
- Built-in diagnostics and statistics.



*Compass Control puts you in charge of your laundry operations. One knob does it all!*

## Environmentally responsible.

Wascomat equipment is accredited according to the ISO14001 Environmental Management System and ISO9001 Quality Management System. With more than a century of experience, Wascomat's state-of-the-art products are engineered for quality, energy savings, and water efficiency.

We optimize your results while lowering your operating costs and environmental impact.

**Wascomat** Laundry Equipment

1-800-645-2204 • [www.wascomat.com](http://www.wascomat.com)

*Wascomat — when laundry means business.*

| Wascomat 200G SU Models                       | SU620        |           | SU625        |           | SU630        |           | SU640        |           | SU655        |           | SU675        |           |
|---|--------------|-----------|--------------|-----------|--------------|-----------|--------------|-----------|--------------|-----------|--------------|-----------|
| Capacity (lb/kg)                              | 20           | 8.5       | 25           | 11        | 30           | 14        | 40           | 18        | 55           | 25        | 75           | 34        |
| Width (in/mm)                                 | 26           | 660       | 28 3/8       | 720       | 28 3/8       | 720       | 29 1/2       | 750       | 32 11/16     | 830       | 35 13/16     | 910       |
| Depth (overall) (in/mm)                       | 30 1/8       | 765       | 29 1/8       | 740       | 32 1/2       | 825       | 36           | 915       | 39           | 990       | 42 5/16      | 1075      |
| Height (in/mm)                                | 43 7/8       | 1115      | 47 1/4       | 1200      | 47 1/4       | 1200      | 52 3/16      | 1325      | 55 1/2       | 1410      | 56 7/8       | 1445      |
| Height to bottom of door (in/mm)              | 14           | 355       | 14 3/8       | 365       | 14 3/8       | 365       | 17 1/8       | 435       | 18 1/2       | 470       | 19 11/16     | 500       |
| Door opening diameter (in/mm)                 | 12 3/16      | 310       | 14 3/8       | 365       | 15 9/16      | 395       | 15 9/16      | 395       | 17 1/8       | 435       | 17 1/8       | 435       |
| Cylinder volume (ft <sup>3</sup> /l)          | 3.0          | 85        | 3.7          | 105       | 4.6          | 130       | 6.4          | 180       | 8.8          | 250       | 11.7         | 330       |
| Cylinder diameter (in/mm)                     | 20 1/2       | 520       | 23 7/16      | 595       | 23 7/16      | 595       | 25 9/16      | 650       | 28 9/16      | 725       | 31 5/16      | 795       |
| Drain outlet diameter (in/mm)                 | 3            | 75        | 3            | 75        | 3            | 75        | 3            | 75        | 3            | 75        | 3            | 75        |
| Height to centerline of drain (in/mm)         | 3 15/16      | 100       | 3 15/16      | 100       | 3 15/16      | 100       | 3 15/16      | 100       | 3 15/16      | 100       | 3 15/16      | 100       |
| Height to electrical connection (in/mm)       | 32 1/2       | 825       | 35 13/16     | 910       | 35 13/16     | 910       | 40 3/4       | 1035      | 44 1/8       | 1120      | 45 1/2       | 1155      |
| Height to water connections (in/mm) (approx)  | 40 9/16      | 1030      | 43 7/8       | 1115      | 43 7/8       | 1115      | 49           | 1245      | 52 3/8       | 1330      | 53 3/4       | 1365      |
| Dynamic load (lb/kN)                          | 382+/-742    | 1.7+/-3.3 | 472+/-899    | 2.1+/-4.0 | 517+/-1057   | 2.3+/-4.7 | 607+/-1326   | 2.7+/-5.9 | 832+/-1664   | 3.7+/-7.4 | 994+/-1978   | 4.2+/-8.8 |
| Dynamic frequency (Hz)                        | 11.6         |           | 10.8         |           | 10.8         |           | 10.3         |           | 9.8          |           | 9.4          |           |
| Noise level (dBA)                             | 66           |           | 71           |           | 71           |           | 76           |           | 79           |           | 77           |           |
| Net wt (lb/kg)                                | 297          | 135       | 385          | 175       | 385          | 175       | 502          | 228       | 631          | 287       | 656          | 298       |
| Crated weight (lb/kg)                         | 343          | 156       | 431          | 196       | 431          | 196       | 528          | 240       | 664          | 302       | 700          | 318       |
| <b>Operating Speeds</b>                       |              |           |              |           |              |           |              |           |              |           |              |           |
| Wash (rpm)                                    | 52           |           | 46           |           | 46           |           | 44           |           | 42           |           | 40           |           |
| Extract (rpm/G-Force)                         | 830 / 200    |           | 776 / 200    |           | 776 / 200    |           | 742 / 200    |           | 702 / 200    |           | 671 / 200    |           |
| <b>Electrical Requirements (standard)</b>     |              |           |              |           |              |           |              |           |              |           |              |           |
| Voltage/frequency/phase                       | 208-240/60/1 |           | 208-240/60/1 |           | 208-240/60/1 |           | 208-240/60/1 |           | 208-240/60/1 |           | 208-240/60/1 |           |
| Full-load current (Amps) / Ckt breaker (Amps) | 3.5 / 15     |           | 3.8/15       |           | 3.8 / 15     |           | 5 / 15       |           | 6.9 / 15     |           | 9 / 15       |           |
| Voltage/frequency/phase                       | 120/60/1     |           | 120/60/1     |           | 120/60/1     |           | 120/60/1     |           | 120/60/1     |           | -            |           |
| Full-load current (Amps) / Ckt breaker (Amps) | 7 / 15       |           | 7.6 / 15     |           | 7.6 / 15     |           | 9.5 / 15     |           | 13.2 / 20    |           | -            |           |
| <b>Water Information</b>                      |              |           |              |           |              |           |              |           |              |           |              |           |
| Inlet fittings (* = 3 inlets)                 | 3/4          | DN20      | 3/4          | DN20      | 3/4          | DN20      | 3/4*         | DN20*     | 3/4*         | DN20*     | 3/4*         | DN20*     |
| Flow (gpm/lpm @ 45 psi) (each inlet)          | 5            | 20        | 5            | 20        | 5            | 20        | 5            | 20        | 16           | 60        | 16           | 60        |
| Recommended water pressure (psi/kPa)          | 30-90        | 200-600   | 30-90        | 200-600   | 20-60        | 150-400   | 20-60        | 150-400   | 20-60        | 150-400   | 20-60        | 150-400   |

Refer installation and servicing to qualified, licensed personnel. Always read installation and operating manuals and consult local codes before installation. Protect machines with properly rated, common-trip, circuit breakers ONLY. Warranty void if not properly installed. Solid-mount machines require a custom concrete foundation, and are not suitable for upper-floor or above-basement installations. Contact Wascomat for more information and for availability of machines for electric services not listed. Specifications subject to change without notice. Wascomat assumes no responsibility for errors or omissions in this information.

## SUPERIOR WASH CYCLE CONTROL

With our Wash Program Manager software you can easily create custom wash programs on your PC.



### Compass Control

With Compass Control you choose the programs that best suit your needs. Modify standard wash programs to find the perfect balance between low water and energy consumption while optimizing wash results and processing time. You can also create your own programs. Multilingual.



Call today for information on the full line of Wascomat washers, dryers, flatwork ironers and low-cost financing and leasing.

## Wascomat Laundry Equipment

1-800-645-2204 • www.wascomat.com

461 Doughty Blvd., Inwood, NY 11096-0338  
 Sales and Administration – Tel: 516-371-4400 • Fax: 516-371-4204 • e-mail: sales@wascomat.com  
 Spare Parts – Tel: 516-371-2000 • Fax: 516-371-4029 • e-mail: parts@wascomat.com  
 Technical Support – Tel: 516-371-0700 • Fax: 516-371-4029 • e-mail: service@wascomat.com  
 En Mexico: Llame gratis a este numero 001-800-010-1010

Your local independent authorized dealer

Authorized  
Wascomat Dealer